

ステンレス金網・亜鉛鍍金線金網在庫表

○印は標準在庫品です。在庫切れの時は二週間以内に製作予定があります。●印は45センチ幅も有ります

線径	メッシュ	開き目(mm)	開口率	SUS・トタン	線径	メッシュ	開き目(mm)	開口率	SUS・トタン	線径	メッシュ	開き目(mm)	開口率	SUS・トタン
2.00	1.5	14.93	77.77	○	1.10	2.5	9.06	79.52	○	0.80	4	5.55	76.39	○ ●
	2	10.70	70.98	○		3	7.37	75.70	○		5	4.28	70.98	○ ○
	2.5	8.16	64.50	○		3.2	6.84	74.20	○		6	3.43	65.78	○ △
	3	6.47	58.34	○		3.5	6.16	71.98	○		6.5	3.11	63.25	○ ○
	3.2	5.94	55.96	○		4	5.25	68.36	○		7	2.83	60.77	○
	4	4.35	46.93	○		4.5	4.54	64.82	○		8	2.38	55.96	○ ○
1.90	2	10.80	72.32	○		5	3.98	61.38	○		9	2.02	51.34	○
	2.5	8.26	66.10	○		5.5	3.52	58.04	○		10	1.74	46.93	○ ○
	3	6.57	60.15	○		6	3.13	54.78	○		12	1.32	38.69	○ ○
	3.2	6.04	57.86	○		6.5	2.81	51.62	○		14	1.01	31.25	○ ○
	3.5	5.36	54.49	○	7	2.53	48.56	○	16S	0.79	24.61	○		
	4	4.45	49.11	○	8	2.08	42.71	○	0.75	5	4.33	72.65	○	
5	3.18	39.19	○	9	1.72	37.24	○	6		3.48	67.71	○		
1.60	1.5	15.33	82.00	○	10	1.44	32.14	○		6.5	3.16	65.30	○	
	2	11.10	76.39	○ △	2.5	9.16	81.28	○ ●		7	2.88	62.93	○	
	2.2	9.95	74.20	○	3	7.47	77.77	○ ○		8	2.43	58.34	○	
	2.5	8.56	70.98	○ △	3.2	6.94	76.39	○ △		10	1.79	49.66	○	
	3	6.87	65.78	○ △	3.5	6.26	74.34	○	12	1.37	41.69	○		
	3.5	5.66	60.77	○	4	5.35	70.98	○ ○	14	1.06	34.41	○		
	4	4.75	55.96	○ △	4.2	5.05	69.66	○	0.73	5	4.35	73.32		
	4.5	4.04	51.34	○	5	4.08	64.50	○ ○		5	4.38	74.34	○ ●	
1.50	5	3.48	46.93	○	6	3.23	58.34	○ ○	6	3.53	69.66	○ ○		
	5.5	3.02	42.71	○	7	2.63	52.48	○	6.5	3.21	67.38	○ △		
	6	2.63	38.69	○	7.5	2.39	49.66	○	8	2.48	60.77	○ ○		
	1.20	2	11.20	77.77	○	8	2.18	46.93	○ ○	0.70	10	1.84	52.48	○ ○
		2.5	8.66	72.65	○	10	1.54	36.76	○ ○		12	1.42	44.80	○ ○
		3	6.97	67.71	○	12S	1.12	27.83	○ ↓0.9		14	1.11	37.72	○ ○
		3.2	6.44	65.78	○	3.2	6.99	77.50	○ ●		16	0.89	31.25	○ ○
		3.5	5.76	62.93	○	4	5.40	72.32	○		0.65	6	3.58	71.65
4		4.85	58.34	○	5	4.13	66.10	○	6.5			3.26	69.50	○
4.5		4.14	53.91	○	6	3.28	60.15	○	7			2.98	67.38	○
5		3.58	49.66	○	6.5	2.96	57.29	○	8			2.53	63.25	○
5.5	3.12	45.59	○	8	2.23	49.11	○	9	2.17	59.24		○		
6	2.73	41.69	○	10	1.59	39.19	○	10	1.89	55.37		○		
1.00	2	11.50	82.00	○	12	1.17	30.38	○	0.63	12		1.47	48.01	○
	2.5	8.96	77.77	○	4	5.45	73.66	○		14		1.16	41.18	○
	3	7.27	73.66	○	5	4.18	67.71	○ △		16	0.94	34.88	○	
	3.5	6.06	69.66	○	6	3.33	62.00	○		6.5	3.28	70.36	○	
	4	5.15	65.78	○	6.5	3.01	59.24	○		7	3.00	68.29	○	
	4.5	4.44	62.00	○	8	2.28	51.34	○		8	2.55	64.25	○ △	
	5	3.88	58.34	○	9	1.92	46.39	○		9	2.19	60.34	○	
	5.5	3.42	54.78	○	10	1.64	41.69	○ ○		10	1.91	56.55	○	
	6	3.03	51.34	○	12	1.22	33.04	○		12	1.49	49.33	○	
	8	1.98	38.69	○	0.83	4	5.52	75.57		○	14	1.18	42.61	○
10S	1.34	27.83	○	5		4.25	69.99	○	16	0.96	36.38	○		
					6.5	3.08	62.03							

線径	メッシュ	開き目(mm)	開口率	SUS・トタン	線径	メッシュ	開き目(mm)	開口率	SUS・トタン	線径	メッシュ	開き目(mm)	開口率	SUS・トタン		
0.60	6	3.63	73.66	○	0.40	10	2.14	70.98	○	0.22	24	0.828	61.26	○		
	6.5	3.31	71.65	○		12	1.72	65.78	○ △		30	0.617	53.05	○		
	7	3.03	69.66	○		14	1.41	60.77	○ ○		32	0.574	52.25	○		
	8	2.58	65.78	○		16	1.19	55.96	○ ○		35	0.506	48.56	○		
	10	1.94	58.34	○		18	1.01	51.34	○		40	0.415	42.71	○		
	12	1.52	51.34	○		20	0.87	46.93	○ ○		50	0.288	32.14	○		
	14	1.21	44.80	○		24	0.66	38.69	○ ○	0.2	40	0.435	46.93	○		
	16	0.99	38.69	○		30	0.45	27.83	○		45	0.364	41.69	○		
18	0.81	33.04	○ ↓0.55	0.37	12	1.75	68.10	○	0.18	50	0.308	36.76	○			
0.57	6.5	3.34	72.95		○ ●	14	1.44	63.37		○	0.16	30	0.667	62.00	○	
	7	3.06	71.05		○	16	1.22	58.82	○	40		0.455	51.34	○		
	8	2.61	67.32		○ ○	18	1.04	54.43	○	50		0.328	41.69	○		
	10	1.97	60.15		○ ○	20	0.90	50.22	○	60		0.243	33.04	○ ○		
	11	1.74	56.72		○	24	0.69	42.30	○	65		0.211	29.09	○		
	12	1.55	53.39		○ ○	0.34	12	1.78	70.45	○ △		0.14	30	0.687	65.78	○
	14	1.24	47.04		○ ○		14	1.47	66.03	○ ○	40		0.475	55.96	○	
	16	1.02	41.08	○ ○	16		1.25	61.75	○ ○	50	0.348		46.93	○		
18	0.84	35.53	○ ○	18	1.07		57.62	○ △	60	0.263	38.69		○			
0.53	8	2.65	69.40	○	20		0.93	53.62	○ ○	0.12	40	0.495	60.77	○		
	10	2.01	62.62	○	24		0.72	46.07	○ ○		50	0.368	52.48	○		
0.50	8	2.68	70.98	○	30		0.51	35.81	○ ○		0.11	60	0.283	44.79	○	
	10	2.04	64.50	○ ○	0.29		14	1.52	70.59			○ ○	0.10	70	0.223	37.72
	12	1.62	58.34	○ ○		16	1.30	66.80	○ ○			0.08		80	0.178	31.25
	14	1.31	52.48	○ ○		18	1.12	63.12	○ △				0.06	50	0.388	58.34
	16	1.09	46.93	○ ○		20	0.98	59.54	○ ○	0.05	60			0.303	51.34	○
	18	0.91	41.69	○		22	0.86	56.07	○		0.04			70	0.243	44.80
20	0.77	36.76	○ ○	24		0.77	52.70	○ ○	0.035	80				0.198	38.69	○
0.47	8	2.71	72.59	○		25	0.73	51.06		○	0.03		40	0.525	68.36	
	10	2.07	66.42	○		28	0.62	46.28	○	0.02		100	0.144	32.14	○	
	12	1.65	60.52	○	30	0.56	43.23	○ ○	0.016			60	0.323	58.33	○	
	14	1.34	54.90	○	32	0.50	40.28	○				0.01	80	0.218	46.93	○
	16	1.12	49.55	○	40	0.35	29.52	○ ↑0.28	0.008				100	0.154	36.76	○
	18	0.94	44.48	○	0.25	16	1.34	70.98		○		0.006	120	0.132	38.70	○
20	0.80	39.68	○	18		1.16	67.71	○	0.005	150	0.109		41.69	○		
0.45	8	2.73	73.66	○ △		20	1.02	64.50		○	0.004	165	0.104	45.59	○	
	10	2.09	67.71	○ ○		24	0.81	58.34		○		0.0035	180	0.091	41.69	○
	12	1.67	62.00	○ ○		30	0.60	49.66		○			0.003	200	0.077	36.76
	14	1.36	56.55	○ ○		32	0.54	46.93		○		0.0025		250	0.062	36.76
	16	1.14	51.34	○ ○		35	0.48	42.97		○	0.002		300	0.045	27.84	○
	18	0.96	46.39	○		40	0.39	36.76	○	0.0015		325	0.043	30.48	○	
	20	0.82	41.69	○ ○	0.23	20	1.04	67.06			0.001	350	0.043	34.41	○	
	22	0.70	37.24	○		24	0.83	61.26	○ △	0.0008		400	0.034	27.83	○	
24	0.61	33.04	○ ○	30		0.62	53.05	○ ○	0.0006		500	0.021	16.76	○		
0.43	10	2.11	69.01	○		32	0.56	50.44		○	0.0005	635	0.020	25.00	○	
	12	1.69	63.50	○		40	0.405	40.68	○ ○	0.0004		795	0.160	24.90	△	
	14	1.38	58.22	○		50	0.278	29.95	○ ○							
	16	1.16	53.16	○												
	18	0.98	48.34	○												
20	0.84	43.75	○													

ステンレス金網の標準品は200メッシュ迄は平織、200メッシュを越えると綾織です
ステンレス金網の標準品は線径0.08迄はSUS-304で0.08未満はSUS-316です
亜鉛鍍金鉄線金網の標準品は91センチ幅x30M巻きです。一部、45、61センチ幅も有ります
上記以外に0.21x30メッシュ 0.21x40メッシュもあります 防虫網は別紙に記載します